



millersoils.co.uk

PRODUCT DATA SHEET

**Motorsport**



AUTOMOTIVE



DATA SHEET NO: 5495

PRODUCT NAME/VISCOSITIES:  
**COMPETITION ASSEMBLY LUBE**

DESCRIPTION:

Specially formulated for competition engine and transmission builders.  
Solvent refined medium base stocks treated with high concentration of anti-wear additives.

APPLICATION:

Use as received for assembly of mechanical components to ensure protection during initial start-up.

USER BENEFITS:

- Assembly lube has been specifically formulated to give mechanical protection during initial start-up of newly assembled components.
- It is designed to be retained on the components treated during assembly and provide very high levels of anti-wear protection, especially components which are subjected to high stress levels i.e. camshafts/followers, crankshaft bearings etc.
- Unlike Assembly Paste-type compounds, Competition Assembly Lube is fully miscible and compatible with all engine oils and will fully dissipate on start up, reducing the need for an extra oil change.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.904
Kinematic Viscosity @ 40°C	320cSt

HEALTH AND SAFETY:

Health and Safety Data Sheet 5495 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

